Your reliable partner for APIs since 60 years



Reliable supply chain

Raw material suppliers are regularly evaluated and provide a certificate of analysis for each delivery. They also must be able to accurately trace their production process.



Quality standards

Certified ISO 9001: 2008 and ISO 14001: 2004, Tournaire has passed many audits at GMP standards. Containers are also approved for the transportation of hazardous goods according to UN regulations.



Quality control

100% on-line inspection of dimensions and surface treatment

Guaranteed cleanliness and surface treatment

During washing and anodisation, the quality of ingredients and parameters is controlled by computer. The handling of containers is also fully automated. During several years, evaluation of the efficiency of the washing process has been performed and a log 3 (1/1000) efficiency factor has been demonstrated.

Packing and palletisation

Each container is packed in a tight bag immediatly after washing and quality control. Palletisation includes deep trays and PE film for the protection of the containers. Specific outer packing solution can be proposed for severe logistic conditions.

Batch and Unit traceability

Batch and unit traceability are ensured through bar codes labels and ink jet printing or engraving on the containers.



Tournaire products meet today's most demanding quality standards and are manufactured in accordance with the strictest specifications.





Drug Master File

Tournaire has registered since 2000 a Type III (pakaging) DMF with the US FDA which is updated and enriched annually.



Tournaire S.A. 70, route de la Paoute Le Plan - BP 71004 06131 GRASSE CEDEX France Phone (33) 493 09 34 34 Fax (33) 493 09 34 00 E-mail: tournaire@tournaire.fr





Tournaire and APIs:

The ultimate protection for your active ingredients



stability

Tournaire Packaging: Major Partner for API containers

since the 1950s

From streptomycin to last generations of cephalosporins, Tournaire has always provided state of the art containers for sterile or non sterile APIs. Our family company closely supports its clients with anticipation of new regulations (DMF), and mastership of modern techniques in the frame of the most demanding quality referentials.

Key figures:

- 175 years of experience.
- 230 staff in France.
- A **20000** m² plant.
- **5000** tons of materials transformed
- **45** millions € turnover.
- **65%** Export worldwide through an international network of agents and distributors.
- 2 manufacturing sites.

Tournaire Equipment:



Tournaire Equipment Division designs and manufactures production units for pharmaceuticals, flavors & fragrances and fine chemicals in the field of extraction, evaporation, rectification, short path distillation, filtration, drying

and distillation. Its engineering department submits the technical files for their working and validation. Tournaire Equipment provides from pilot units to industrial plants compliant with ATEX and DESP rules.





Aluminium for stability and protection

Easy Sterilisation / Depyrogenation

• _____

+

4

Dry heat sterilisation allows in one single step the sterilisation AND depyrogenation of the container. Furthermore, it eliminates the presence of moisture. Autoclaving can also be used for sterilisation alone. When tested before despatch, our containers have been found to be pyrogen free.



Depyrogenation

High resistance

Seamless aluminium containers are resistant to shocks, perforations, cuts, cold and heat. They also give absolute protection to light and gas permeation

Safe and reliable protection

The European Pharmacopeia considers pure (min 99.5%) aluminium containers as safe and neutral for contact with Food and Drugs when produced and used according to GMP (Good manufacturing Practice).

Specific Surface treatment

Scouring and anodisation according to an approved process give a clean, smooth and resistant surface. Tournaire has worked closely with major pharmaceutical users over the years to standardise the best surface treatment, described in our DMF.



Tournaire bottles: Full range with type III DMF to help your registration



VOL.(L)	802
2,5	✓
5,5 / 6,25	✓
12,5	✓
20	✓
25	✓
28,5 / 29,5	1
30 / 32	1

835

1

1

1

1



O 220

-

-

1

-1

-

1

Efficient design for user friendly solution

Seamless container

Each container is made of one disc of pure aluminium. Its whole surface is continuous, smooth and has no recesses nor seams.

Optimised tightness

The calibration of the neck together with the elasticity of the rubber plug provides an hermetic seal, even with extreme variation of pressure.



Filling Easy sealing and opening

Different closure systems are available, which provide user friendly sealing and opening as well as efficient tamper evident features.

Tournaire WORKS for YOU by providing close regulatory support, but also accessories in addition to its container range. Various validated closing systems and accessories will bring smooth and reliable use for your comfort and safety.

Easy to use closing systems

102mm opening with push-in chlorobutyl plug and aluminium cap for sealing.

-135 mm opening with push-in chlorobutyl plug reinforced by an aluminium disc and aluminium cap for sealing.





Sealing systems Cap Opener



2nd generation stainless steel crimping tool provides reinforced crimping efficiency and still higher reliability of sealing. It is easy to sterilise and does not require maintenance nor adjustement An automation of this manual tool can be studied upon request.



Stainless steel cap opener allows to smoothly open the aluminium cap without touching it, thus avoiding the risk of contamination or cutting the glove.

Geometrical features





-220mm opening with aluminium lid, nitrile ring wad and clamping ring.



Tool for Inserting/ removing the plug



Connected with reduced vaccuum source, the stainless steel removal/insertion tool allows to insert/remove the chlorobutyl plug easily (no rubbing nor effort) and avoids any contact with the plug (reduces risk of contamination).

Sample bottles



Small containers and plugs made of the same material for sampling and stability tests: from 30cc to 275cc for 10 g to 100 g sampling.